

Inverter generator series P1700i



Cummins Onan

Performance you rely on.™



Features and benefits

- 1350 watts running, 1650 watts peak
- 3.5 hour continuous operating time (at rated load)
- Manual start
- 2.4 HP, overhead valve engine
- 0.9 gallon fuel tank
- LED display
- 120 V 20 A GFCI protected duplex receptacle, 12 V DC charging
- Automatic "low-oil shutdown"
- Indicator lights pilot lamps
- Overload condition and auto power saver
- 2 year limited warranty
- Meets EPA, CSA standards

Weight, size and sound level

Dry Weight: 45 lb (20.5 kg)

Size: Length 19 in (480 mm), width 12 in (295 mm), height 18 in (445 mm)

Sound: Readings at 7 m: 59 dB(A)

Models and ratings

AC rated output	1.35 kW/1350 W	DC voltage	12 V
AC max output	1.65 kW/1650 W	Engine horsepower	2.4
AC Voltage	120 V	Fuel tank capacity	0.9 Gal/3.5 L
AC frequency	60 Hz		
120 V AC rated amperage - Rated/max	11.2 A/13.8 A		

Ratings apply to altitudes up to 1000 ft (304.8 m), 85 °F (30 °C). Total power available will decrease 3.5% for each 1000 ft (304.8 m) above 1000 ft and 2.0% for each 10 °F (5.5 °C) increase in ambient temperature above 85 °F (30 °C).