

Commercial generator series PX7500 & PX7500e



Cummins Onan

Performance you rely on.™



Features and benefits

- 6000 watts running, 7300 watts peak
- 7 hour continuous operating time (at rated load)
- Manual start (*optional electric start)
- 13.5 HP, 4-stroke overhead valve engine
- Large 7.3 gallon fuel tank
- 120 V 20 A GFCI protected duplex, 120 V 20 A twist lock, 120 V 30 A twist lock 120/240 V 30 A twist lock, 12 V DC charging
- Full power switch
- Volt and hour meter
- Large muffler w/U.S. Forestry approved spark arrestor
- Idle control system
- High performance alternator w/max surge capacity
- 2 year limited warranty
- Meets EPA, CSA standards

Weight, size and sound level

- Weight:** PX7500 - 198 lb (89.8 kg)
PX7500e - 209 lb (94.8 kg)
- Size:** PX7500 - Length 27 in (685.8 mm), width 21 in (533.4 mm), height 21 in (533.4 mm)
PX7500e - Length 34 in (863.6 mm), width 21 in (533.4 mm), height 21 in (533.4 mm)
- Sound:** Readings at 7 m: 76 dB(A)

Models and ratings

AC rated output	6.0 kW/6000 W	DC voltage	12 V
AC max output	7.3 kW/7300 W	Engine horsepower	13.5
AC Voltage	120 V/240 V	Fuel tank capacity	7.3 Gal/27.6 L
AC frequency	60 Hz		
120 V AC rated amperage - Rated/max	50 A/60.8 A		
240 V AC rated amperage - Rated/max	25 A/30.4 A		

Ratings apply to altitudes up to 1000 ft (304.8 m), 85 °F (30 °C). Total power available will decrease 3.5% for each 1000 ft (304.8 m) above 1000 ft and 2.0% for each 10 °F (5.5 °C) increase in ambient temperature above 85 °F (30 °C).

Cummins®, Onan®, the "C" logo and Performance you rely on.™ are servicemarks, trademarks and/or registered trademarks of Cummins Inc. Specifications subject to change without notice. ©2008 Cummins Power Generation. All Rights Reserved.
A-1512a (9/08) (formerly F-1673)