



## Hydraulic Single-Stage Compressors

These units include the American Eagle single-stage reciprocating pump, which is directly attached to the hydraulic motor (no pulleys and belts), a hydraulic oil cooler, 12v. fan, valve block, and fiberglass cover.

Optional hydraulic oil reservoir attaches under the compressor.



### Model SHD-21A

- 21 cu. in. displacement
- 8 cfm @ 100 psi
- Hyd. req: 7 gpm @ 1800 psi
- Max. pressure: 150 psi
- Single Stage, 2-cylinder
- Imbedded air filter
- 23"L x 14.5"W x 17"H
- Weight: 125 lbs
- Uses Model 143 Pump



### Model SHD-30A

- 30 cu. in. displacement
- 13 cfm @ 100 psi
- Hyd. req: 7 gpm @ 1800 psi
- Max. pressure: 150 psi
- Single Stage, 2-cylinder
- Imbedded air filter
- 26"L x 14.5"W x 17"H
- Weight: 125 lbs
- Uses Model 200 Pump



#### **Model SHD-43AF**

- 43 cu. in. displacement
  - 23 cfm @ 100 psi
  - Hyd. req: 10 gpm @ 1800 psi
  - Max. pressure: 150 psi
  - Single Stage, 4 cylinder
  - Canister air filter
  - 31"L x 19"W x 25"H
  - Weight: 165 lbs
  - Uses Model V360 Pump
- (Shown with optional 11-gal. oil reservoir)



#### **Model SHD-60AF**

- 60 cu. in. displacement
- 30 cfm @ 100 psi
- Hyd. req: 10 gpm @ 1800 psi
- Max. pressure: 150 psi
- Single Stage, 4-cylinder
- Canister air filter
- 26"L x 18"W x 18"H
- Weight: 175 lbs
- Uses Model V480 Pump



#### **Model SHD-132A**

- 132 cu. in. displacement
- 70 cfm @ 100 psi
- Hyd. req: 16 gpm @ 3000 psi
- Max. pressure: 150 psi
- Single Stage, 4-cylinder
- Imbedded air filter
- 31"L x 21"W x 22.25"H
- Weight: 300 lbs
- Uses Model HV60 Pump