



Hydraulic Two-Stage Compressors

American Eagle uses the R-Series two-stage reciprocating compressor in its hydraulic packages that are belt driven or directly attached to the hydraulic motor, with oil cooler and fan included.

An optional attached oil reservoir is available.



Model SHD-66DD

- 66 cu. in. displacement
- 46 cfm @ 175 psi
- Hyd. req: 16 gpm @ 2000 psi
- Max. pressure: 175 psi
- 150 - 175 PSI operating range
- Two-Stage, 4-cylinder
- 33.5"L x 24"W x 25.5"H
- Weight: 425 lbs
- Optional 15-gal. oil reservoir



Model SHD-138

- 130 cu. in. displacement
- 60 cfm @ 175 psi
- Hyd. req: 16 gpm @ 2300 psi
- Max. pressure: 175 psi
- Two-Stage, 2-cylinder
- 46"L x 24"W x 26"H
- Weight: 655 lbs
- Optional 26-gal. oil reservoir



Model SHD-245

- 142 cu. in. displacement
- 110 cfm @ 175 psi
- Hyd. req: 24 gpm @ 2300 psi
- Max. pressure: 175 psi
- Two-Stage, 4-cylinder
- 43"L x 28"W x 32"H
- Weight: 900 lbs
- Optional 26-gal. oil reservoir (Shown)
- 46"L x 28"W x 41"H (with reservoir)