



When fire threatens, seconds count...

...be prepared with **FIRE CADDY™**



the **DC1205 12-Volt DC**

... is *the* 12voltDC fire foam suppression system. This patent-pending, high-powered, economical system has been engineered specifically for the demanding environments of fire-fighting.

FireCaddy 'DC' uses FlameOut®, a non-toxic, environmentally safe, 100% biodegradable foam, that is approved under NFPA 18 and meets UL162 certification for fire performance and foam standards.

**A fully-integrated, portable, solution - 12 volts that charge at fires**

- Rechargeable liquid gel battery
- 25 feet of 3/4" lay-flat discharge hose
- Add up to 400 feet of hose
- Adjustable brass shut-off
- AC adapter wall charger
- Custom low-amp, high speed motor
- 5 US ga. of FlameOut® Class A/B foam
- 4 ft water suction hose
- Professional Scotty® nozzles
- Industrial rated brass pump
- In-line strainer
- Foam expansion tube

Feature	What our Customers Value
Fire-fighting Discharge	- effectively fight fires safely from a 40 ft. distance with a flow rate of 6-7 gpm - safe and effective operating pressure of 100-110 psi
Long run times (approx. 7 mins)	- allows for sufficient time for people to safely egress from structure; - contains fire throughout the time for local emergency crews to arrive
Operation Ready; Ease-of-Use	- response time is fast; - when responding to a fire, there aren't any complicated tasks to be operational; - low maintenance
Foam; completely mixed	- 7-8 times more effective than just water alone; - no foam "dry" spots from the nozzle
Compact, fully integrated design	- highly portable; - can be placed almost anywhere, including inside enclosed spaces
Rugged, Reliable	- engineered to withstand rough environments and the test of time so that it will be ready when you need it

*The portable system that is effective on all Class A & Class B fires. It is ideal for use on temporary work sites, emergency response vehicles, service vehicles, tow trucks, transport trucks, or anywhere that emergency first response fire performance is required.*

**The FIRE CADDY™ JB1205 configuration**

The FireCaddy DC1205 built into a rugged "Job Box" that can be placed at a stationary location or mounted onto a truck bed.

- 28" h x 48" w x 24" d
- Lockable sturdy steel box
- Integral tanks for 42 US gal water & 4 US gal. FlameOut®
- 150 lbs empty, 650 lbs filled



**Take Control.**

**Make a Difference.**

**FIRE CADDY™**

...a registered Trademark of **Just-In Case Fire Ltd.**